

AL-27

Full bore type	Lift type	Safety valve	Relief valve
Safety relief valve	Lever type	Closed type	Dash-pot structure
Handle type	Stainless	High pressure gas testing products	
Diaphragm	Non-leakage		

■Features

1. Relief valve, designed for pressure up to 1.6 MPa.
2. Remarkably effective for lines of heavy pulsation or considerable pressure fluctuation due to unique valve structure. Prevents chattering and hunting.
3. Stable operation can be maintained against back pressure changes produced in continuous blow.

■Specifications


Structure	Closed type	
Application	Cold and hot water, Oil, Other non-dangerous fluids (Less than 20 cst)	
Working pressure	0.05-1.6 MPa	
Maximum temperature	120°C	
Material	Valve case	Ductile cast iron
	Spring case	Ductile cast iron
	Valve, valve seat	Stainless steel
Connection	JIS Rc screwed	

· Please refer to the chart in P. 82 for set pressure range.

■Dimensions and Weights

Nominal size	d	L	H ₁	H	Weight (kg)
15A	Rc 1/2	40	40	143	0.9
20A	Rc 3/4	45	50	162	1.3
25A	Rc 1	50	60	182	1.7
32A	Rc 1-1/4	60	70	220	2.9
40A	Rc 1-1/2	65	75	238	3.9
50A	Rc 2	80	85	272	6.4


· Dashpot structure



Flow Rate Chart [water]

Shown in the chart is the flow rate at 25% accumulation.

For flow rates at other accumulation levels, use the approximate flow rate magnification chart.



Approximate flow rate magnification chart

When the accumulation is not 25%, select an approximate flow rate magnification matching the accumulation based on this chart, and multiply the flow rate at 25% accumulation by the selected magnification.

